

Application chart

- Official recommendation list for edgebanding
- Approved and qualified by Holz-Her GmbH



Jowatherm® | EVA hot melt adhesives
Jowat-Toptherm® | PO hot melt adhesives
Jowatherm-Reaktant® | PUR hot melt adhesives
Jowat® | flushing agent

Jowat Klebstoffe		TECHNICAL DATA														HOLZHER	
		APPLICATION LIST - ADHESIVES															
 www.jowat.com		Hot melt adhesives															
		EVA										PO	PUR				
		Type	Jowatherm® 280.30	Jowatherm® 280.50 / 280.58	Jowatherm® 281.40 / 281.48	Jowatherm® 288.10	Jowatherm® 288.60	Jowatherm® 288.70	Jowatherm® 284.70	Jowatherm® 286.30	Jowatherm® 286.60	Jowatherm® 286.80	Jowat-Toptherm® 237.10	Jowatherm-Reaktant® 608.00	Jowatherm-Reaktant® 607.40	Jowatherm-Reaktant® 607.50	Jowat® 930.94
Delivery Form	GRANULATE	●	●	●	●	●	●	●				●	●	●	●	●	
	CARTRIDGE "CLASSIC"								●	●	●		●	●	●	●	
	CARTRIDGE "GLU JET 2K"												●	●	●	●	
Colour / Appearance	TRANSPARENT	●	●	●					●				●				
	LIGHT BEIGE		●	●	●	●	●	●		●	●	●		●	●		
	WHITE	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
	BROWN					●		●		●	●						
	BLACK					●		●		●	●						
Straight Edgebanding	MELAMINE	●	●	●	●	●	●	●	●	●	●	●	●	●	●	Flushing agent Jowatherm-Reaktant® (PUR)	
	ABS, PP, PVC ≤ 2 mm	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
	ABS, PP, PVC > 2 mm	○	●	●	○	○	○		○	○	○	●	○	○	●		
	LAMINATES (HPL, CPL)	●	●	●	○	○			○	○	○	●	●	○	○		
	SOLID WOOD	○	●	●	○	○			○	○	○	●	○	○	●		
	VENEER FLEECEBACKED	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
	THICKVENEER	○	●	●	○	○	○		○	○	○	●	○	○	●		
● Technically preferred / Available		last updated: 09/2017															
○ Technically convenient																	

Please find any suggestions for processing and cleaning in the technical data sheet! Upon request!
Product availability might differ by region. Please contact us.

First class bonding

Jowat
Adhesives